

DFWRXP

"DFWR": INDICATOR WITH VERY BRIGHT RED LED DISPLAY



Digital weight indicator, with very bright and efficient red LED, easily visible from all angles, from long distances. Brightness intensity is easily adjustable. Its high performance and available programmes make it suitable for all industrial and commercial applications. CE-M approvable (OIML R-76 / EN 45501).



The best solution
for advanced industrial
applications

MAIN STANDARD FEATURES

- Waterproof 17-key functional keyboard.
- Very bright red LED display with 6 digits 25 mm high; easily visible from all angles and from long distances, with adjustable brightness intensity.
- Complete of 6 Leds for showing the active functions.
- Waterproof ABS IP65 case, easy to clean and resistant to harsh and corrosive environments.
- Dimensions in mm: 278x125x186.
- Suitable for use on the table, column, or wall.
- Fitted with attached thermal printer and real time clock in the DFWRP version.
- A/D 24 bit, 4 channel converter, up to 200 conv./sec. autoselect, and up to 8 signal linearisation points.
- Up to 10.000e or multirange 3 x 3000e @ 0,3 μ V/d in CE-M approved version for legal for trade use.
- Up to 1.000.000 divisions displayable with built-in resolution up to 3.000.000 points.
- Calibration and digital Set-Up from the keyboard or from PC with DINITOOLS.
- Built-in rechargeable battery (60 hours with a 350 Ohm load cell) and internal 110-240 Vac adapter.
- Connection with up to 8 load cells having an input resistance of 350 Ohm or with up to 16 cells of 700 Ohm.

MAIN CERTIFICATIONS

- EC Type Approval (EN45501)
- OIML R76

I/O SECTION

- RS232/C port configurable for connection with printer/labeller, or for attached printer.
- RS232/C (or optionally RS485) bi-directional port configurable for PC, PLC, remote display, and radio modem. Quick RJ RS232 plug connection.

FUNCTIONS

- **KEYBOARD:**
Zeroing, Automatic tare, Presetable tare, printing and/or data transmission, selectable function command, on/off switching, Database of 10 tares, 2 Numeric IDs, keyboard lock, repetition of last printout made.
- **SELECTABLE FUNCTIONS:**
 - High Resolution Weighing x 10.
 - Net/Gross or lb/kg conversion.
 - Accumulation.
 - Formula weighing.
 - +/- Checkweighing.
 - Percentage weighing.
 - Approved transmission of the weight to PC/PLC or data recording on MMC/USB (with Alibi memory ALMEM option).
 - Counting(Max. resolution of 1.500.000 divisions).
 - In/Out Truck weighing.
 - Hold and Peak.
 - Set Point Control (with DFIO option).

AVAILABLE FUNCTIONS FROM REMOTE CONTROL

- Infrared 19-key remote control: zero, tare / manual tare, enable / disable function, print, switch-off.
- Radiofrequency 6-key remote control: zero, tare, enable / disable function, print, switch-off.



www.diniargeo.com



“YOUR WORLDWIDE PARTNER FOR WEIGHING,”

DINI ARGEO
FRANCE sarl
Nogent-sur-Marne
info.fr@diniargeo.com

DINI ARGEO
GMBH
Sinsheim - Germany
info.de@diniargeo.com

DINI ARGEO
UK Ltd
Taunton - United Kingdom
info.uk@diniargeo.com

DINI ARGEO WEIGHING
INSTRUMENTS Ltd
Shanghai - China
info.cn@diniargeo.com

DINI ARGEO
WEIGHBRIDGES
Calto (RO) – Italy
info@diniargeo.com




HEAD OFFICE

Via Della Fisica, 20
41042 Spezzano di Fiorano Modena - Italy
Tel. +39.0536 843418 Fax. +39.0536 843521
info@diniargeo.com

SERVICE ASSISTANCE

Via Dell'Elettronica, 15
41042 Spezzano di Fiorano Modena - Italy
Tel. +39.0536 921784 Fax. +39.0536 926654
service@diniargeo.com



SALES AND TECHNICAL ASSISTANCE SERVICE